

# ABB monitoring and communications VSN300 Wifi Logger Card



The VSN300 Wifi Logger Card is a new, advanced expansion board for ABB's UNO and TRIO string inverters which provides residential and commercial users with an advanced and cost-effective solution for monitoring and controlling their photovoltaic system.

The VSN300 Wifi Logger Card is easy to install, for new and most existing string inverters by using the inverter's internal expansion slot.

The built-in IP networking connectivity and innovative Wi-Fi commissioning techniques enable this card to be easily configured for most Wi-Fi networks and access points without installing any additional external devices.

## Complete, remote and local monitoring with Wifi Logger Card and new free mobile app.

Users have a complete remote and local monitoring experience when combining VSN300 Wifi Logger Card with ABB's new free mobile app; "Plant Viewer for Mobile". It is available for both iOS and Android based devices.

The local web server in VSN300 Wifi Logger Card adds the ability to use a standard web browser to access inverter data.

The Wi-Fi Certified™ mark assures interoperability, security, easy installation and reliability. With innovative commissioning and upgrade features, the VSN300 Wifi Logger Card provides the best user experience for ABB's customers.

Not only is the VSN300 Wifi Logger Card suitable for most of ABB's string inverters currently deployed, it takes advantage of the Hyperlink bus found in new inverters for obtaining real-time data that can be used for grid control power management.

## Highlights

- The Wi-Fi Certified™ mark assures interoperability with IEEE 802.11b/g/n networks over the 2.4 GHz band
- Easily installed on new and existing UNO and TRIO string inverters
- IEEE 802.11b/g/n (2.4 GHz) support
- Local, remote monitoring in one solution
- High performance non-volatile data logging
- High-speed inverter data exchange through Hyperlink [where available]
- Modbus TCP server for SCADA integration
- SunSpec certified Modbus mapping for easy integration
- Secured and encrypted data transfer to Aurora Vision® Plant Management Platform
- Remote reading and writing of inverter parameters for advanced operations
- California Rule 21 ready

# VSN300 Wifi Logger Card



## Technical data and types

<b>Type code</b>	<b>VSN300 Wifi Logger Card</b>
<b>Communication interfaces</b>	
Inverter interface	Hyperlink (CAN@1 Mbps + RS485@115 kBaud) / Legacy (Serial link TTL @ 19.2 kBaud)
User interface	Wi-Fi Certified™ IEEE 802.11 b/g/n (2,4 GHz)
<b>Communication protocols</b>	
Protocoll LAN/WAN	HTTPS, DHCP, NTP, SSL, SSH, XML, Modbus TCP (Sunspec)
<b>Monitoring</b>	
Web user interface (WUI)	Integrated
Local monitoring	Wirelessly allowed via any Wi-Fi® device connecting the integrated WUI or running Plant Viewer for Mobile
Remote monitoring	Plant Portfolio Manager® / Plant Viewer™ / Plant Viewer for mobile
<b>Data logging specifications</b>	
Data sampling rate	High frequency data sampling (1 minute sample rate)
Local data storage	Log data for 30 days based on 15-minute intervals
Upgradeability	Remotely via Aurora Vision® Plant Management Platform / locally via integrated Web User Interface <sup>1)</sup>
<b>Advanced functionalities</b>	
Remote O&M operations	Inverter's parameters setting <sup>2)</sup> / inverter's firmware upgrade <sup>2)</sup>
Smart grid functionalities	Grid control power-management enabled <sup>2)</sup>
<b>Power supply</b>	
DC power supply output	~ 2 W
<b>Environmental parameters</b>	
Ambient temperature range	[-20; +85]°C
Environmental protection	IP 20
Relative humidity	<85% Non-condensing
<b>Mechanical parameters (per unit)</b>	
Dimensions (H x W x D)	3.81' x 1.81' x 0.63' (97 mm x 46 mm x 16 mm)
Weight	0.06 lbs (26 g)
Mounting System	Inverter's expansion slot
<b>Compliance</b>	
Marking	CE / RCM / Wi-Fi Certified™
Emissions	47 CFR FCC Part 15 Subpart C, EN 55022 Conducted and radiated emission
Immunity	EN55024

<sup>1)</sup> Available from FW version FW 1.8.x

<sup>2)</sup> Check for availability

**Remark. Features not specifically listed in the present data sheet are not included in the product**

## Application with VSN300 Wifi Logger Card



### Inverter matrix compatibility

Inverter family	Monitoring	Remote O&M Operations <sup>1)</sup>
UNO-2.0	Yes	No
UNO-2.5	Yes	No
UNO-7.6	Yes	Yes
UNO-8.6	Yes	Yes
PVI-3.0	Yes	No
PVI-3.6	Yes	No
PVI-3.8	Yes	No
PVI-4.2	Yes	No
PVI-4.6	Yes	No
PVI-5000	Yes	No
PVI-6000	Yes	No
PVI-6.0	Yes	No
PVI-8.0	Yes	No
PVI-10.0	Yes	No
PVI-12.5	Yes	No
TRIO-5.8	Yes	Yes
TRIO-7.5	Yes	Yes
TRIO-8.5	Yes	Yes
TRIO-20.0	Yes	No
TRIO-27.6	Yes	No

<sup>1)</sup> Inverter's parameters setting and inverter's firmware upgrade (from FW version 1.8.x)

### Support and service

ABB supports its customers with dedicated, global service organization in more than 60 countries and strong regional and national technical partner networks providing complete range of life cycle services.

For more information please contact your local ABB representative or visit:

[www.abb.com/solarinverters](http://www.abb.com/solarinverters)

[www.abb.com/solar](http://www.abb.com/solar)

[www.abb.com](http://www.abb.com)

© Copyright 2015 ABB. All rights reserved.  
Specifications subject to change without notice.

